

LISTING OF THE CLAIMS

This listing of claims will replace all prior versions, and listings, of claims in the application:

1. **(Currently Amended)** A shape of endoscope detecting apparatus comprising:
a shape detecting means for detecting the shape of a portion of an insertion unit of an endoscope inserted into a subject, and producing graphic data expressing the shape thereof;
a first marker means for marking a position on the subject at which the endoscope is
5 inserted;

a first location information of marker acquiring means for acquiring location information of said first marker means; and

a display control means ~~to process coordinates~~ for graphically indicating intracavity insertion shape data produced by the shape detecting means, the display control means being
10 configured to graphically indicate on a display means the shape of an intracavitary portion of the insertion unit obtained by subjecting the intracavity insertion shape data produced by the shape detecting means to coordinate processing with the location information of the marker acquired by the marker acquiring means as a reference ~~detected by said shape detecting means using as a reference the location information of said marker means acquired by said location information of~~
15 ~~marker acquiring means.~~

2. **(Previously Presented)** A shape of endoscope detecting apparatus according to Claim 1, wherein said location information is a first point of coordinates in a predetermined coordinate system, and further comprising:

a second marker means independent of said first marker means and movable to any
5 position on the subject;

a second location information of marker acquiring means for acquiring location information of said second marker means as a second point of coordinates contained in the coordinate system;

10 a point of coordinates shifting means for shifting the first point of coordinates acquired by
said first location information of marker acquiring means with respect to the second point of
coordinates acquired by said second location information of marker acquiring means; and

a display control means to process coordinates for graphically indicating on said display
means the location information of said first marker means according to the first point of
coordinates shifted by said point of coordinates shifting means.

3. (Previously Presented) A shape of endoscope detecting apparatus according to
Claim 1, wherein location information of said first marker means is a first point of coordinates
contained in a predetermined coordinate system, and further comprising:

5 a second marker means independent of said first marker means and movable to any
position on the subject;

a second location information of marker acquiring means for acquiring location
information of said second marker means as a second point of coordinates contained in the
coordinate system;

10 a point of coordinates shifting means for shifting the first point of coordinates acquired by
said first location information of marker acquiring means and points of coordinates defining the
shape of an inserted portion of the insertion unit with respect to the second point of coordinates
acquired by said second location information of marker acquiring means; and

15 a display control means to process coordinates for graphically indicating on said display
means the location information of said first marker means and the shape of the inserted portion
according to the first point of coordinates and the points of coordinates defining the shape of the
inserted portion which are shifted by said point of coordinates shifting means.

4. (Previously Presented) A shape of endoscope detecting apparatus according to
Claim 1, wherein said location information is a first point of coordinates in a predetermined
coordinate system, and further comprising:

5 a second marker means independent of said first marker means and movable to any
position on the subject;

a second location information of marker acquiring means for acquiring location information of said second marker means as a second point of coordinates contained in the coordinate system when the insertion unit of the endoscope has just been inserted into the subject;

10 a point of coordinates shifting means for shifting the first point of coordinates acquired by said first location information of marker acquiring means with respect to the second point of coordinates acquired by said second location information of marker acquiring means; and

a display control means to process coordinates for graphically indicating on said display means the location information of said first marker means according to the first point of
15 coordinates shifted by said point of coordinates shifting means.

5. (Original) A shape of endoscope detecting apparatus comprising:

a shape detecting means for detecting the shape of a portion of an insertion unit of an endoscope inserted into a subject, and producing graphic data expressing the shape thereof;

a marker means for marking a position on the subject at which the endoscope is inserted;

5 a location information of marker acquiring means for acquiring location information of said marker means; and

a display control means to process coordinates for graphically indicating on a display means the shape of a portion of the insertion unit lying in the subject beyond said marker means, wherein said shape detecting means detects the shape of said portion of said insertion unit of said
10 endoscope inserted into said subject using as a reference the location information of said marker means acquired by said location information of marker acquiring means, and disabling graphical indication on said display means of the shape of a portion thereof lying outside the subject beyond said marker means.

6. (Original) A shape of endoscope detecting apparatus comprising:

a shape detecting means for detecting the shape of a portion of an insertion unit of an endoscope inserted into a subject, and producing graphic data expressing the shape thereof;

an endoscope manipulation information acquiring means for acquiring manipulation
5 information representing manipulations performed on the endoscope inserted into the subject;
a marker means for marking a position on the subject at which the endoscope is inserted;
a location information of marker acquiring means for acquiring location information of
said marker means;

a display control means to process coordinates for graphically indicating on a display
10 means the shape of the inserted portion detected by said shape detecting means, wherein said
shape detecting means detects the shape of the inserted portion using as a reference the location
information of said marker means acquired by said location information of marker acquiring
means; and

a superimposing means for superimposing on said display means the manipulation
15 information acquired by said endoscope manipulation information acquiring means on the shape
of the inserted portion graphically indicated by said display control means.

7. (Original) A shape of endoscope detecting apparatus according to Claim 6, wherein
said superimposing means superimposes an absolute scale on the shape of an inserted portion
graphically indicated on said display means

8. (Original) A shape of endoscope detecting apparatus according to Claim 6, wherein
said superimposing means superimposes the length of a portion of the insertion unit of the
endoscope inserted in to the subject, which is detected by a length of inserted portion detecting
means, on the shape of the inserted portion graphically indicated on said display means.

9. (Previously Presented) A shape of endoscope detecting method comprising:
a first marker placing step of placing a first marker near a region of a subject through
which an endoscope is inserted;
a first location information of marker acquiring step of acquiring location information of
5 said first marker;

a shape of inserted portion detecting step of detecting the shape of a portion of an insertion unit of the endoscope inserted into the subject using as a reference the location information of said first marker, and producing graphic data expressing the shape thereof;

a display control step to process coordinates for graphically indicating on a display means the shape of the inserted portion detected at said shape of inserted portion detecting step.

10. (Previously Presented) A shape of endoscope detecting method according to Claim 9, wherein location information of said first marker is a first point of coordinates contained in a predetermined coordinate system, and further comprising:

a step of acquiring location information of a second marker, which is independent of said first marker and movable to any position on the subject, as a second point of coordinates contained in the coordinated system;

a step of shifting the first point of coordinates acquired at said first location information of marker acquiring step with respect to the second point of coordinates acquired at said second location information of marker acquiring step; and

a step of extending display control to process coordinates for graphically indicating on said display means the location information of said first marker according to the first point of coordinates shifted at said point of coordinates shifting step.

11. (Previously Presented) A shape of endoscope detecting method according to Claim 9, wherein location information of said first marker is a point of coordinates contained in a predetermined coordinate system, and further comprising:

a step of acquiring location information of a second marker, which is independent of said first marker and movable to any position on the subject, as a second point of coordinates contained in the coordinate system;

a step of shifting the first point of coordinates acquired at said first location information of marker acquiring step and points of coordinates defining the shape of an inserted portion of the insertion unit with respect to the second point of coordinates acquired at said second location information of marker acquiring step; and

a step of extending display control to process coordinates for graphically indicating on said display means the location information of said first marker and the shape of the inserted portion according to the first point of coordinates and the points of coordinates defining the shape of the inserted portion which are shifted at said point of coordinates shifting step.

12. (Previously Presented) A shape of endoscope detecting method according to Claim 9, wherein location information of said first marker is a first point of coordinates contained in a predetermined coordinate system, and further comprising the steps of:

acquiring location information of a second marker, which is independent of said first marker and movable to any position on the subject, as a second point of coordinates contained in the coordinate system when the insertion unit of the endoscope has just been inserted into the subject;

shifting the first point of coordinates acquired at said first location information of marker acquiring step with respect to the second point of coordinates acquired at said second location information of marker acquiring step; and

extending display control to process coordinates for graphically indicating on said display means the location information of said first marker according to the first point of coordinates shifted at said point of coordinates shifting step.

13. (Previously Presented) A shape of endoscope detecting method comprising the steps of:

placing a predetermined marker near a region of a subject through which an endoscope is inserted;

acquiring location information of said marker;

detecting the shape of a portion of an insertion unit of the endoscope inserted into the subject using as a reference the location information of said marker, and producing graphic data expressing the shape thereof; and

extending display control to process coordinates for graphically indicating on a display means the shape of a portion of the insertion unit lying in the subject beyond said marker, and to

disable graphical indication on said display means of the shape of a portion thereof lying outside the subject beyond said marker.

14. (Previously Presented) A shape of endoscope detecting method comprising the steps of:

placing a predetermined marker near a region of a subject through which an endoscope is inserted;

5 acquiring location information of said marker;

detecting the shape of a portion of an insertion unit of the endoscope inserted into the subject using as a reference the location information of said marker, and producing graphic data expressing the shape thereof;

10 acquiring manipulation information representing manipulations performed on the endoscope inserted into the subject;

extending display control to process coordinates for graphically indicating on a display means the shape of the inserted portion; and

15 superimposing the manipulation information acquired by said endoscope manipulation information acquiring step on the shape of the inserted portion graphically indicated on said display means at said display control step.

15. (Original) A shape of endoscope detecting method according to Claim 14, wherein at said manipulation information superimposing step, an absolute scale is superimposed on the shape of the inserted portion of the endoscope graphically indicated on said display means.

16. (Original) A shape of endoscope detecting method according to Claim 14, further comprising:

a step of detecting the length of a portion of the insertion unit of the endoscope inserted into the subject; and

- 5 a step of superimposing the length of the inserted portion detected at said length of inserted portion detecting step on the shape of the inserted portion of the endoscope graphically indicated on said display means.